

STEAM CLEANERS

DRY STEAM GENERATORS 220V 50 HERTZ



APPLICATIONS

- Soil Sterilization
- CCIP Cure in Place
- Atomization
- Virus & Mold Sterilization
- Greenhouse Humidification & Sterilization
- Tobacco Humidification
- Heating Tank Fluids

WHY CHOOSE ALKOTA

There is no reason that machines need to be complicated to do their job.

Our team of engineers and product developers have been designing, building and improving high pressure cleaning systems since 1964. When you buy an **Alkota** pressure washer, you're buying quality and longevity. It is an investment in the future of your business.

At **Alkota** we believe that simplicity means quality.

Being American owned our machines are built with high quality materials the old-fashioned way, by hand. We design and assemble them right here in the heart of the **USA**, so that you know you're getting an American-built machine.



DRY STEAM GENERATORS SPECIFICATION CHART

MODEL 126 SPECIFICATION



DESCRIPTION	
Heat Input	390,000 BTU/HR
Steam Pressure	50 to 80 PSI
Pump Motor	2 H.P.
Voltage	220V., 50 HZ, 1 PH, 15 AMP
Pump	Belt Drive, Oil Bath Triplex Plunger Pump
Burner Coil	Vertical Configuration Sprial Wound Schedule 80 AST-53 Steel Pipe, Cold Water Wrap
Controls	Pressure Switch, Pressure Gauge, Temperature Gauge, Rotary 3 Position Switch - Off/Pump/Burner
Burner	Diesel Fired Burner
Fuel Consumption	2.8 gallons per hour
Fuel Tank	10.5 Gallon
Temperature	Up to 300 F Dry Steam
Steam Trap	Dry Steam Trap & Sperator for Removal of 85% of Water
Safety Valve	Safety Relief Steam Valve
Safety	Low Water, High Temperature & High Pressure Safety
Wheels	Two Pneumatic Wheels for ease of portability
Weight	450 Lbs.
Dimensions	L-34", W-28", H-42"

MODEL 246 SPECIFICATION



DESCRIPTION	
Heat Input	630,000 BTU/HR
Steam Pressure	80 to 100 PSI
Pump Motor	2 H.P.
Voltage	115 V., 60 HZ, 1 PH, 15 AMP
Pump	Belt Drive, Oil Bath Triplex Plunger Pump
Burner Coil	Horizontal Configuration Sprial Wound Schedule 80 AST-53 Steel Pipe, Cold Water Wrap
Controls	Oil Primary Control, Pressure Switch, Temperature Control, Relief Valve, Pressure Gauge, Temperature Gauge, Manual Reset High Temperature Control, 90 Second Delay Timer on Burner Star Up, 90 Second Delay on Pump Shut Off, Rotary 3 Position Switch - Off/Pump/Burner.
Burner	Diesel Fired Burner
Fuel Consumption	4.5 gallons per hour
Fuel Tank	10.5 Gallon
Temperature	Up to 300 F Dry Steam
Steam Trap	Dry Steam Trap & Sperator for Removal of 85% of Water
Safety Valve	Safety Relief Steam Valve
Safety	Low Water, High Temperature & High Pressure Safety
Wheels	Four Non-Flat Wheels for ease of portability
Weight	725 Lbs.
Dimensions	L-63", W-29", H-43"



Alkota Cleaning Systems Inc.
Alcester, South Dakota 57001

For more information call:
(800) 255-6823 / (605) 934-2222 or
Fax: (800) 325-5682 / (605) 934-1808
Web Access: www.alkota.com

CERTIFICATIONS



© 2020 Alkota Cleaning Systems
Specifications subject to change without notice
Printed in U.S.A. / Form #: ALK-DSG1-0320

Distributed by:

